

**FAG****16016-C3**

Deep groove ball bearing

Deep groove ball bearing 160, single row,  
steel sheet metal cage

## Technical information



## Your current product variant

Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	80 mm	Bore diameter
D	125 mm	Outside diameter
B	14 mm	Width
$C_r$	34,000 N	Basic dynamic load rating, radial
$C_{0r}$	31,500 N	Basic static load rating, radial
$C_{ur}$	1,560 N	Fatigue load limit, radial
$n_G$	7,700 1/min	Limiting speed
$n_{gr}$	4,600 1/min	Reference speed
$m$	0.59 kg	Weight



### Mounting dimensions

$d_{a \min}$	83.2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	121.8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0.6 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0.6 mm	Minimum chamfer dimension
$D_1$	110.72 mm	Shoulder diameter outer ring
$d_1$	96.84 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Calculation factors

$f_0$	16.6	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed