

**FAG****6038-M-C3**

Deep groove ball bearing

Deep groove ball bearing 60...-M, single row,
solid brass cage

Technical information



Your current product variant

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	190 mm	Bore diameter
D	290 mm	Outside diameter
B	46 mm	Width
C_r	216,000 N	Basic dynamic load rating, radial
C_{0r}	220,000 N	Basic static load rating, radial
C_{ur}	9,400 N	Fatigue load limit, radial
n_G	3,850 1/min	Limiting speed
n_{gr}	3,100 1/min	Reference speed
m	11.3 kg	Weight



Mounting dimensions

$d_{a \min}$	200.2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	279.8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2.1 mm	Maximum fillet radius

Dimensions

r_{\min}	2.1 mm	Minimum chamfer dimension
D_1	260.25 mm	Shoulder diameter outer ring
d_1	220.82 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

f_0	15.6	Calculation factor
-------	------	--------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed