View product details on medias

16.06.2026, 21:40:57 UTC

SCHAEFFLER

FAG

6312-2Z-C3

Deep groove ball bearing

Deep groove ball bearing 63..-2Z, single row, shields, steel sheet metal cage

Technical information





Your current product variant

Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	130 mm	Outside diameter
B	31 mm	Width
C_r	89,000 N	Basic dynamic load rating, radial
C_{0r}	52,000 N	Basic static load rating, radial
C_{ur}	3,600 N	Fatigue load limit, radial
n_G	6,700 1/min	Limiting speed
$n_{\vartheta r}$	6,700 1/min	Reference speed
≈m	1.76 kg	Weight

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form

Mounting dimensions

$d_{a\ min}$	72 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	118 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2.1 mm	Maximum fillet radius

Dimensions

r_{min}	2.1 mm	Minimum chamfer dimension
D_1	108.62 mm	Shoulder diameter outer ring
D_2	113.14 mm	Caliber diameter outer ring
d_1	81.25 mm	Shoulder diameter inner ring

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Calculation factors

f_0	13.2	Calculation factor

Characteristics

- Radial load
- Axial load in one direction
- Axial load in two directions
- Lifetime lubrication, freedom from maintenance
- Grease Lubrication
- Sealed on both sides

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form