

**FAG****16005-A-2Z-C3**

Deep groove ball bearing

Deep groove ball bearing 160..-A-2Z, single row, shields, steel sheet metal cage

Technical information



Your current product variant

Changed internal design	A	Design variant A
Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	47 mm	Outside diameter
B	8 mm	Width
C_r	9,400 N	Basic dynamic load rating, radial
C_{0r}	5,600 N	Basic static load rating, radial
C_{ur}	325 N	Fatigue load limit, radial
n_G	18,800 1/min	Limiting speed
n_{gr}	11,600 1/min	Reference speed
m	62 g	Weight



Mounting dimensions

$d_{a \min}$	27 mm	Minimum diameter shaft shoulder
$D_{a \max}$	45 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0.3 mm	Maximum fillet radius

Dimensions

r_{\min}	0.3 mm	Minimum chamfer dimension
D_1	40.4 mm	Shoulder diameter outer ring
D_2	42.87 mm	Caliber diameter outer ring
d_1	32.5 mm	Shoulder diameter inner ring







Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

f_0	15.1	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides