

**FAG****16010-A**

## Deep groove ball bearing

Deep groove ball bearing 160..-A, single row, steel sheet metal cage

## Technical information

**Your current product variant**

Changed internal design	A	Design variant A
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	50 mm	Bore diameter
D	80 mm	Outside diameter
B	10 mm	Width
C <sub>r</sub>	17,000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	13,300 N	Basic static load rating, radial
C <sub>ur</sub>	760 N	Fatigue load limit, radial
n <sub>G</sub>	12,200 1/min	Limiting speed
n <sub>gr</sub>	6,300 1/min	Reference speed
≈m	0.175 kg	Weight



### Mounting dimensions

$d_{a \min}$	53.2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	76.8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0.6 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0.6 mm	Minimum chamfer dimension
$D_1$	72.1 mm	Shoulder diameter outer ring
$d_1$	61.9 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	16.3	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed