

**FAG****16011-A**

Deep groove ball bearing

Deep groove ball bearing 160..-A, single row, steel sheet metal cage

Technical information



Your current product variant

Changed internal design	A	Design variant A
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	90 mm	Outside diameter
B	11 mm	Width
C_r	20,600 N	Basic dynamic load rating, radial
C_{0r}	16,300 N	Basic static load rating, radial
C_{ur}	940 N	Fatigue load limit, radial
n_G	10,900 1/min	Limiting speed
n_{gr}	6,000 1/min	Reference speed
m	0.259 kg	Weight



Mounting dimensions

$d_{a \min}$	58.2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	86.8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0.6 mm	Maximum fillet radius

Dimensions

r_{\min}	0.6 mm	Minimum chamfer dimension
D_1	78.61 mm	Shoulder diameter outer ring
d_1	69.6 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

f_0	16.2	Calculation factor
-------	------	--------------------

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed