

**FAG****6008**

Deep groove ball bearing

Deep groove ball bearing 60, single row, steel sheet metal cage

Technical information



Your current product variant

Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	68 mm	Outside diameter
B	15 mm	Width
C_r	17,800 N	Basic dynamic load rating, radial
C_{0r}	11,500 N	Basic static load rating, radial
C_{ur}	600 N	Fatigue load limit, radial
n_G	14,600 1/min	Limiting speed
n_{gr}	10,600 1/min	Reference speed
m	0.181 kg	Weight



Mounting dimensions

$d_{a \min}$	44.6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	63.4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
D_1	59.06 mm	Shoulder diameter outer ring
D_2	61.56 mm	Caliber diameter outer ring
d_1	49.3 mm	Shoulder diameter inner ring







Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

f_0	15.2	Calculation factor
-------	------	--------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed