

**FAG****61910-2RSR**

Deep groove ball bearing

Deep groove ball bearing 619..-2RSR, single row, seals, steel sheet metal cage

## Technical information

**Your current product variant**

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	50 mm	Bore diameter
D	72 mm	Outside diameter
B	12 mm	Width
C <sub>r</sub>	15,400 N	Basic dynamic load rating, radial
C <sub>0r</sub>	11,700 N	Basic static load rating, radial
C <sub>ur</sub>	700 N	Fatigue load limit, radial
n <sub>G</sub>	4,700 1/min	Limiting speed
m	0.13 kg	Weight

**Mounting dimensions**

d <sub>a min</sub>	53.2 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	68.8 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	0.6 mm	Maximum fillet radius



### Dimensions

$r_{\min}$	0.6 mm	Minimum chamfer dimension
$D_1$	65.24 mm	Shoulder diameter outer ring
$D_2$	67.3 mm	Caliber diameter outer ring
$d_1$	56.9 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	16.1	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides