

**FAG****4302-BB-TVH** [↗](#)

Deep groove ball bearing

Deep groove ball bearing 43...BB-TVH,
double row, plastic cage

Technical information



Your current product variant

Design variant	B	Bearing without filling slot
Tolerance class	PN	Normal (ISO 492:2023)
Changed internal design	B	B
Cage	TVH	Solid cage made of glass-fiber reinforced polyamid PA66
Lubricant	GA14	Ball bearing grease, low noise
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Radial internal clearance	CN (Group N)	Normal internal clearance

Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	42 mm	Outside diameter
B	17 mm	Width
C_r	15,600 N	Basic dynamic load rating, radial
C_{0r}	9,500 N	Basic static load rating, radial
C_{ur}	495 N	Fatigue load limit, radial
n_G	17,500 1/min	Limiting speed
n_{gr}	11,600 1/min	Reference speed
$\approx m$	0.115 kg	Weight



Mounting dimensions

$d_{a \min}$	20.6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	36.4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
D_1	33.05 mm	Shoulder diameter outer ring
d_1	23.8 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

f_0	13	Calculation factor
-------	----	--------------------

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Not sealed