

**FAG****7203-B-XL-2RS-TVP**

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-2RS-TVP, single row, X-life, seals, plastic cage

**X-life**

Technical information



Your current product variant

Design variant	B	B
Sealing	2RS	Contact seal on both sides
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA14	Ball bearing grease, low noise

Main Dimensions & Performance Data

d	17 mm	Bore diameter
D	40 mm	Outside diameter
B	12 mm	Width
C_r	11,200 N	Basic dynamic load rating, radial
C_{0r}	5,700 N	Basic static load rating, radial
C_{ur}	395 N	Fatigue load limit, radial
n_G	11,100 1/min	Limiting speed
$\approx m$	0.068 kg	Weight



Mounting dimensions

$d_{a \min}$	21.2 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	35.8 mm	Maximum diameter of housing shoulder
$D_{b \max}$	37.6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0.6 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0.3 mm	Maximum fillet radius of housing






Dimensions

r_{\min}	0.6 mm	Minimum chamfer dimension
$r_{1 \min}$	0.3 mm	Minimum chamfer dimension
D_1	31.46 mm	Shoulder diameter on outer ring wide side face
D_2	33.05 mm	Caliber diameter on outer ring wide side face
D_3	36.34 mm	Caliber diameter on outer ring small side face
d_1	25.99 mm	Shoulder diameter on inner ring wide side face
d_2	22.93 mm	Caliber diameter on inner ring wide side face
a	18 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides