

**FAG****7216-B-XL-JP**

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-JP,
single row, X-life, steel sheet metal cage**X-life**

Technical information



Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	JP	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	140 mm	Outside diameter
B	26 mm	Width
C_r	85,000 N	Basic dynamic load rating, radial
C_{0r}	72,000 N	Basic static load rating, radial
C_{ur}	4,800 N	Fatigue load limit, radial
n_G	6,400 1/min	Limiting speed
n_{gr}	4,950 1/min	Reference speed
m	1.473 kg	Weight



Mounting dimensions

$d_{a \min}$	91 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	129 mm	Maximum diameter of housing shoulder
$D_{b \max}$	134.4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	2 mm	Minimum chamfer dimension
$r_{1 \min}$	1 mm	Minimum chamfer dimension
D_1	117.24 mm	Shoulder diameter on outer ring wide side face
d_1	102.9 mm	Shoulder diameter on inner ring wide side face
a	59.2 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed