



FAG

**7203-B-XL-TVP** [↗](#)

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-TVP,  
single row, X-life, plastic cage

X-life

## Technical information



## Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	17 mm	Bore diameter
D	40 mm	Outside diameter
B	12 mm	Width
$C_r$	11,200 N	Basic dynamic load rating, radial
$C_{0r}$	5,700 N	Basic static load rating, radial
$C_{ur}$	395 N	Fatigue load limit, radial
$n_G$	26,000 1/min	Limiting speed
$n_{gr}$	17,100 1/min	Reference speed
$\approx m$	0.066 kg	Weight



### Mounting dimensions

$d_{a \min}$	21.2 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	35.8 mm	Maximum diameter of housing shoulder
$D_{b \max}$	37.6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0.6 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0.3 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	0.6 mm	Minimum chamfer dimension
$r_{1 \min}$	0.3 mm	Minimum chamfer dimension
$D_1$	31.46 mm	Shoulder diameter on outer ring wide side face
$d_1$	25.99 mm	Shoulder diameter on inner ring wide side face
$a$	18 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed