



Technical information



Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P5	Class 5 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UL	Bearing set with light preload
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	52 mm	Outside diameter
B	15 mm	Width
C_r	16,200 N	Basic dynamic load rating, radial
C_{0r}	9,000 N	Basic static load rating, radial
C_{ur}	620 N	Fatigue load limit, radial
n_G	19,200 1/min	Limiting speed
n_{gr}	13,700 1/min	Reference speed
$\approx m$	0.126 kg	Weight



Mounting dimensions

$d_{a \min}$	30.6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	46.4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	47.8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0.6 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0.6 mm	Minimum chamfer dimension
D_1	42.02 mm	Shoulder diameter on outer ring wide side face
d_1	35.54 mm	Shoulder diameter on inner ring wide side face
a	23.7 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

V_{\max}	-4 μm	Preload per set max.
Tol (+)	6 μm	Tolerance for axial clearance or preload per set
$F_{V \max}$	112 N	Preload force



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed