



FAG

**7219-B-XL-TVP** [↗](#)

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-TVP,  
single row, X-life, plastic cage

X-life

## Technical information




## Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	95 mm	Bore diameter
D	170 mm	Outside diameter
B	32 mm	Width
$C_r$	123,000 N	Basic dynamic load rating, radial
$C_{0r}$	106,000 N	Basic static load rating, radial
$C_{ur}$	6,400 N	Fatigue load limit, radial
$n_G$	5,200 1/min	Limiting speed
$n_{gr}$	4,450 1/min	Reference speed
$\approx m$	2.61 kg	Weight





### Mounting dimensions

$d_{a \min}$	107 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	158 mm	Maximum diameter of housing shoulder
$D_{b \max}$	163 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2.1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	2.1 mm	Minimum chamfer dimension
$r_{1 \min}$	1.1 mm	Minimum chamfer dimension
$D_1$	141.5 mm	Shoulder diameter on outer ring wide side face
$d_1$	125.3 mm	Shoulder diameter on inner ring wide side face
$a$	71.6 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed