



Technical information



Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	38 mm	Width
C_r	167,000 N	Basic dynamic load rating, radial
C_{0r}	154,000 N	Basic static load rating, radial
C_{ur}	8,600 N	Fatigue load limit, radial
n_G	4,350 1/min	Limiting speed
n_{gr}	3,950 1/min	Reference speed
$\approx m$	4.445 kg	Weight



Mounting dimensions

$d_{a \min}$	122 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	188 mm	Maximum diameter of housing shoulder
$D_{b \max}$	193 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2.1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	2.1 mm	Minimum chamfer dimension
$r_{1 \min}$	1.1 mm	Minimum chamfer dimension
D_1	165.7 mm	Shoulder diameter on outer ring wide side face
d_1	144.9 mm	Shoulder diameter on inner ring wide side face
a	84 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed