

**FAG****7301-B-XL-JP**

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-JP,
single row, X-life, steel sheet metal cage**X-life**

Technical information



Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	JP	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	37 mm	Outside diameter
B	12 mm	Width
C_r	12,200 N	Basic dynamic load rating, radial
C_{0r}	5,300 N	Basic static load rating, radial
C_{ur}	365 N	Fatigue load limit, radial
n_G	28,000 1/min	Limiting speed
n_{gr}	16,300 1/min	Reference speed
m	0.063 kg	Weight



Mounting dimensions

$d_{a \min}$	17.6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	31.4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	32.8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0.6 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0.6 mm	Minimum chamfer dimension
D_1	27.23 mm	Shoulder diameter on outer ring wide side face
d_1	22.29 mm	Shoulder diameter on inner ring wide side face
a	16.3 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed