

**FAG****7318-B-XL-TVP** [↗](#)

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-TVP,  
single row, X-life, plastic cage**X-life**

## Technical information



## Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	90 mm	Bore diameter
D	190 mm	Outside diameter
B	43 mm	Width
C <sub>r</sub>	171,000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	144,000 N	Basic static load rating, radial
C <sub>ur</sub>	8,400 N	Fatigue load limit, radial
n <sub>G</sub>	4,650 1/min	Limiting speed
n <sub>gr</sub>	3,950 1/min	Reference speed
≈m	4.97 kg	Weight



### Mounting dimensions

$d_{a \min}$	104 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	176 mm	Maximum diameter of housing shoulder
$D_{b \max}$	183 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2.5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$r_{1 \min}$	1.1 mm	Minimum chamfer dimension
$D_1$	152.14 mm	Shoulder diameter on outer ring wide side face
$d_1$	130.3 mm	Shoulder diameter on inner ring wide side face
$a$	80.2 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed