

**FAG****7407-B-XL-MP**

Angular contact ball bearing

Angular contact ball bearing 74..-B-XL-MP,
single row, X-life, solid brass cage**X-life**

Technical information



Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	100 mm	Outside diameter
B	25 mm	Width
C_r	65,000 N	Basic dynamic load rating, radial
C_{0r}	43,000 N	Basic static load rating, radial
C_{ur}	3,000 N	Fatigue load limit, radial
n_G	12,100 1/min	Limiting speed
n_{gr}	5,400 1/min	Reference speed
m	1.058 kg	Weight



Mounting dimensions

$d_{a \min}$	46 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	89 mm	Maximum diameter of housing shoulder
$D_{b \max}$	94.4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1.5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	1.5 mm	Minimum chamfer dimension
$r_{1 \min}$	1 mm	Minimum chamfer dimension
D_1	79.8 mm	Shoulder diameter on outer ring wide side face
d_1	66.7 mm	Shoulder diameter on inner ring wide side face
a	42.9 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

-  F_r Radial load
-  F_a Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed