

**FAG****7415-B-XL-MP**

Angular contact ball bearing

Angular contact ball bearing 74..-B-XL-MP,  
single row, X-life, solid brass cage**X-life**

## Technical information



## Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	75 mm	Bore diameter
D	190 mm	Outside diameter
B	45 mm	Width
C <sub>r</sub>	167,000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	138,000 N	Basic static load rating, radial
C <sub>ur</sub>	8,300 N	Fatigue load limit, radial
n <sub>G</sub>	6,400 1/min	Limiting speed
n <sub>gr</sub>	3,750 1/min	Reference speed
m	6.59 kg	Weight



### Mounting dimensions

$d_{a \min}$	91 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	174 mm	Maximum diameter of housing shoulder
$D_{b \max}$	181 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2.5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$r_{1 \min}$	1.1 mm	Minimum chamfer dimension
$D_1$	144.34 mm	Shoulder diameter on outer ring wide side face
$d_1$	123.1 mm	Shoulder diameter on inner ring wide side face
$a$	78.1 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed