

**FAG****3201-BB-2Z-TVH**

Angular contact ball bearing

Angular contact ball bearing 32..-B-2Z-TVH,
double row, shields, plastic cage

Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Changed internal design	B	B
Sealing	2Z	Non-contact shield on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	32 mm	Outside diameter
B	15.9 mm	Width
C_r	10,500 N	Basic dynamic load rating, radial
C_{0r}	5,800 N	Basic static load rating, radial
C_{ur}	300 N	Fatigue load limit, radial
n_G	18,400 1/min	Limiting speed
n_{gr}	20,000 1/min	Reference speed
$\approx m$	0.057 kg	Weight



Mounting dimensions

$d_{a \min}$	16.2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	27.8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0.6 mm	Maximum fillet radius

Dimensions

r_{\min}	0.6 mm	Minimum chamfer dimension
D_1	25.99 mm	Shoulder diameter outer ring
D_2	27.77 mm	Caliber diameter outer ring
d_1	17.8 mm	Shoulder diameter inner ring
d_2	17.2 mm	Caliber diameter inner ring
a	16.5 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides