

**FAG****3310-BD-XL-2HRS-TVH**

Angular contact ball bearing

Angular contact ball bearing 33..-BD-XL-2HRS-TVH, double row, X-life, seals, plastic cage

**X-life**

## Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	2HRS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	CN	Group N (CN)

**Main Dimensions & Performance Data**

d	50 mm	Bore diameter
D	110 mm	Outside diameter
B	44.4 mm	Width
C <sub>r</sub>	93,000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	70,000 N	Basic static load rating, radial
C <sub>ur</sub>	4,850 N	Fatigue load limit, radial
n <sub>G</sub>	4,900 1/min	Limiting speed
≈m	1.78 kg	Weight



### Mounting dimensions

$d_{a \min}$	61 mm	Minimum diameter shaft shoulder
$D_{a \max}$	99 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum fillet radius







### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$D_1$	93.26 mm	Shoulder diameter outer ring
$D_2$	96.75 mm	Caliber diameter outer ring
$d_1$	71.47 mm	Shoulder diameter inner ring
$d_2$	69.05 mm	Caliber diameter inner ring
$a$	64.2 mm	Distance between the apexes of the pressure cones
$\alpha$	30 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides