

**FAG****129-TVH**

Self-aligning ball bearing

Self-aligning ball bearing 12..-TVH, plastic cage

Technical information



Your current product variant

| | | |
|---------------------------|--------------|--|
| Bore type | Z | Cylindrical |
| Sealing | Without | Not sealed |
| Cage | TVH | Solid cage made of glass-fiber reinforced polyamide PA66 |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Lubricant | Without | Bearing not greased |

Main Dimensions & Performance Data

| | | |
|-------------|--------------|-----------------------------------|
| d | 9 mm | Bore diameter |
| D | 26 mm | Outside diameter |
| B | 8 mm | Width |
| C_r | 3,950 N | Basic dynamic load rating, radial |
| C_{0r} | 810 N | Basic static load rating, radial |
| C_{ur} | 51 N | Fatigue load limit, radial |
| n_G | 33,500 1/min | Limiting speed |
| n_{gr} | 24,100 1/min | Reference speed |
| $\approx m$ | 21.2 g | Weight |

Mounting dimensions

| | | |
|--------------|---------|--------------------------------------|
| $d_{a \min}$ | 13.2 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 21.8 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0.6 mm | Maximum fillet radius |



Dimensions

| | | |
|-----------|---------|------------------------------|
| r_{min} | 0.6 mm | Minimum chamfer dimension |
| D_1 | 20 mm | Shoulder diameter outer ring |
| d_1 | 14.5 mm | Shoulder diameter inner ring |









Temperature range

| | | |
|-----------|--------|----------------------------|
| T_{min} | -30 °C | Operating temperature min. |
| T_{max} | 120 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--|
| e | 0.32 | Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y |
| Y_1 | 1.94 | Dynamic axial load factor |
| Y_2 | 3.01 | Dynamic axial load factor |
| Y_0 | 2.04 | Static axial load factor |

Characteristics

-  F_r Radial load
-  F_a Axial load in one direction
-  F_a Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment