

**FAG****2206-K-2RS-TVH-C3**

Self-aligning ball bearing

Self-aligning ball bearing 22..-K-2RS-TVH,  
tapered bore taper 1:12, seals, plastic cage

## Technical information





## Your current product variant

Bore type	K	Tapered, taper 1:12
Sealing	2RS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Lubricant	GA14	Ball bearing grease, low noise

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	20 mm	Width
$C_r$	15,900 N	Basic dynamic load rating, radial
$C_{0r}$	4,650 N	Basic static load rating, radial
$C_{ur}$	295 N	Fatigue load limit, radial
$n_G$	7,100 1/min	Limiting speed
$\approx m$	0.26 kg	Weight





### Mounting dimensions

$d_{a \min}$	35.6 mm	Minimum diameter shaft shoulder
$d_{a \max}$	38 mm	Maximum diameter shaft shoulder
$D_{a \max}$	56.4 mm	Maximum diameter of housing shoulder
$d_{b \min}$	33 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	5 mm	Minimum cavity width of the sleeve
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$D_1$	51.56 mm	Shoulder diameter outer ring
$D_2$	53.33 mm	Caliber diameter outer ring
$d_1$	39.55 mm	Shoulder diameter inner ring
$d_2$	37.3 mm	Caliber diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$e$	0.25	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2.54	Dynamic axial load factor
$Y_2$	3.93	Dynamic axial load factor
$Y_0$	2.66	Static axial load factor

### Additional information






H306

Adapter sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment
-  Dynamic angular error and misalignment