

**FAG****QJ208-XL-TVP**

Four-point contact bearing

Four point contact bearing QJ2..-XL-TVP, X-life, plastic cage

**X-life**

## Technical information



## Your current product variant

Tolerance class	PN	Normal (ISO 492:2023)
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	CN	Group N (CN)

## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter
D	80 mm	Outside diameter
B	18 mm	Width
$C_r$	58,000 N	Basic dynamic load rating, radial
$C_{0r}$	46,500 N	Basic static load rating, radial
$C_{ur}$	3,250 N	Fatigue load limit, radial
$n_G$	11,600 1/min	Limiting speed
$n_{gr}$	7,500 1/min	Reference speed
$\approx m$	399 g	Weight

## Mounting dimensions

$d_{a \min}$	47 mm	Minimum diameter shaft shoulder
$D_{a \max}$	73 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius



### Dimensions

$r_{\min}$	1.1 mm	Minimum chamfer dimension
$D_1$	66.8 mm	Shoulder diameter outer ring
$d_1$	53.65 mm	Shoulder diameter inner ring
$a$	42 mm	Distance between the apexes of the pressure cones
$\alpha$	35 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed