

**FAG****N214-E-XL-TVP2** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing N2..-E-TVP, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N2

## Technical information

**Your current product variant**

Cage	TVP2	Solid Window Cage made from PA66
Tolerance class	PN	Normal (ISO 492:2023)
Change mark	E	Increased Capacity Design
Radial internal clearance	CN (Group N)	Normal internal clearance
Number of rows	1	Single-row design

**Main Dimensions & Performance Data**

d	70 mm	Bore diameter
D	125 mm	Outside diameter
B	24 mm	Width
C <sub>r</sub>	242,000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	222,000 N	Basic static load rating, radial
C <sub>ur</sub>	40,500 N	Fatigue load limit, radial
n <sub>G Grease</sub>	6,600 1/min	Limiting speed for grease lubrication
n <sub>G Oil</sub>	7,800 1/min	Limiting speed for oil lubrication
≈m	1.14 kg	Weight

**Mounting dimensions**

d <sub>a</sub>	79 mm	Diameter shaft shoulder
D <sub>a</sub>	116 mm	Diameter of housing shoulder
r <sub>a1 max</sub>	1.5 mm	Maximum recess radius



### Dimensions

$r_{1 \text{ min}}$	1.5 mm	Minimum chamfer dimension
$s_1$	1.2 mm	Axial displacement
E	113.5 mm	Raceway diameter outer ring

### Temperature range

$T_{\text{min}}$	-30 °C	Operating temperature min.
$T_{\text{max}}$	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed