

**FAG****N307-E-XL-M1-C3** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing N3..-E-M1, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N3

Technical information

**Your current product variant**

Cage	M1	Two Piece Brass Cage Roller Guided
Change mark	E	Increased Capacity Design
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	80 mm	Outside diameter
B	21 mm	Width
C _r	76,000 N	Basic dynamic load rating, radial
C _{0r}	63,000 N	Basic static load rating, radial
C _{ur}	10,600 N	Fatigue load limit, radial
≈m	0.536 kg	Weight

Mounting dimensions

D _a	71 mm	Diameter of housing shoulder
r _{a1 max}	1 mm	Maximum recess radius

Dimensions

r _{1 min}	1.1 mm	Minimum chamfer dimension
E	70.2 mm	Raceway diameter outer ring



Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

-  F_r Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed