

**FAG****N312-E-XL-M1** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing N3..-E-M1, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N3

Technical information

**Your current product variant**

Cage	M1	Two Piece Brass Cage Roller Guided
Tolerance class	PN	Normal (ISO 492:2023)
Change mark	E	Increased Capacity Design
Radial internal clearance	CN (Group N)	Normal internal clearance
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	130 mm	Outside diameter
B	31 mm	Width
C_r	177,000 N	Basic dynamic load rating, radial
C_{0r}	157,000 N	Basic static load rating, radial
C_{ur}	28,500 N	Fatigue load limit, radial
n_G Grease	8,400 1/min	Limiting speed for grease lubrication
$\approx m$	2 kg	Weight

Mounting dimensions

D_a	118 mm	Diameter of housing shoulder
$r_{a1 \max}$	2 mm	Maximum recess radius







Dimensions

$r_1 \text{ min}$	2.1 mm	Minimum chamfer dimension
E	115 mm	Raceway diameter outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed