



FAG

NU216-E-XL-M1-C3

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Technical information



Your current product variant

| | | |
|---------------------------|--------------|------------------------------------|
| Design | E | Increased Capacity Design |
| Cage | M1 | Two Piece Brass Cage Roller Guided |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Number of rows | 1 | Single-row design |

Main Dimensions & Performance Data

| | | |
|----------|-------------|-----------------------------------|
| d | 80 mm | Bore diameter |
| D | 140 mm | Outside diameter |
| B | 26 mm | Width |
| C_r | 166,000 N | Basic dynamic load rating, radial |
| C_{0r} | 168,000 N | Basic static load rating, radial |
| C_{ur} | 23,100 N | Fatigue load limit, radial |
| n_G | 9,000 1/min | Limiting speed |
| n_{gr} | 4,200 1/min | Reference speed |
| m | 1.7 kg | Weight |



Mounting dimensions

| | | |
|---------------|--------|--------------------------------------|
| $d_{a \min}$ | 91 mm | Minimum diameter shaft shoulder |
| $d_{a \max}$ | 94 mm | Maximum diameter of shaft shoulder |
| $d_{b \min}$ | 97 mm | Minimum shaft shoulder |
| $D_{a \max}$ | 129 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2 mm | Maximum recess radius |
| $r_{a1 \max}$ | 2 mm | Maximum recess radius |

Dimensions

| | | |
|--------------|-----------|---------------------------------|
| r_{\min} | 2 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 2 mm | Minimum chamfer dimension |
| s | 1.3 mm | Axial displacement |
| E | 125.3 mm | Raceway diameter outer ring |
| F | 95.3 mm | Raceway diameter inner ring |
| $D_{1 \min}$ | 120.45 mm | Minimum rib diameter outer ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 150 °C | Operating temperature max. |

Characteristics

| | |
|---|--------------------|
|  | Radial load |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |