



FAG

NU2330-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Technical information



Your current product variant

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	320 mm	Outside diameter
B	108 mm	Width
C _r	1,380,000 N	Basic dynamic load rating, radial
C _{0r}	1,600,000 N	Basic static load rating, radial
C _{ur}	250,000 N	Fatigue load limit, radial
n _G	3,650 1/min	Limiting speed
n _{gr}	1,460 1/min	Reference speed
m	42.44 kg	Weight



Mounting dimensions

$d_{a \min}$	167 mm	Minimum diameter shaft shoulder
$d_{a \max}$	190 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	195 mm	Minimum shaft shoulder
$D_{a \max}$	303 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
$r_{a1 \max}$	3 mm	Maximum recess radius

Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
$r_{1 \min}$	4 mm	Minimum chamfer dimension
s	9.7 mm	Axial displacement
E	283 mm	Raceway diameter outer ring
F	193 mm	Raceway diameter inner ring
$D_{1 \min}$	269.8 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing