View product details on medias

16.06.2026, 23:18:22 UTC

SCHAEFFLER

FAG

X-life

NU413-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NU..-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Technical information



Your current product variant

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design





Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	160 mm	Outside diameter
B	37 mm	Width
C_r	230,000 N	Basic dynamic load rating, radial
C_{0r}	203,000 N	Basic static load rating, radial
C_{ur}	27,000 N	Fatigue load limit, radial
n_G	8,100 1/min	Limiting speed
$n_{\vartheta r}$	4,600 1/min	Reference speed
≈m	4.06 kg	Weight

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form

Mounting dimensions

$d_{a\ min}$	79 mm	Minimum diameter shaft shoulder
$d_{a\ max}$	88 mm	Maximum diameter of shaft shoulder
$d_{b\ min}$	91 mm	Minimum shaft shoulder
$D_{a\ max}$	146 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2 mm	Maximum recess radius
$r_{a1\ max}$	2 mm	Maximum recess radius

Dimensions

r_{min}	2.1 mm	Minimum chamfer dimension
$r_{1\ min}$	2.1 mm	Minimum chamfer dimension
s	3.5 mm	Axial displacement
E	135.3 mm	Raceway diameter outer ring
F	89.3 mm	Raceway diameter inner ring
$D_{1\ min}$	127.7 mm	Minimum rib diameter outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Characteristics

Radial load

Grease Lubrication

Oil Lubrication

Not sealed

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form