



FAG

**NU418-XL-M1-C4**

Cylindrical roller bearing

Cylindrical roller bearing NU..-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

## Technical information



## Your current product variant

|                           |              |                                    |
|---------------------------|--------------|------------------------------------|
| Design                    | Standard     |                                    |
| Cage                      | M1           | Two Piece Brass Cage Roller Guided |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3  |
| Tolerance class           | PN           | Normal (ISO 492:2023)              |
| Number of rows            | 1            | Single-row design                  |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 90 mm       | Bore diameter                     |
| D               | 225 mm      | Outside diameter                  |
| B               | 54 mm       | Width                             |
| C <sub>r</sub>  | 465,000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 425,000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 54,000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 5,500 1/min | Limiting speed                    |
| n <sub>gr</sub> | 3,500 1/min | Reference speed                   |
| ≈m              | 11.7 kg     | Weight                            |



### Mounting dimensions

|               |        |                                      |
|---------------|--------|--------------------------------------|
| $d_{a \min}$  | 110 mm | Minimum diameter shaft shoulder      |
| $d_{a \max}$  | 122 mm | Maximum diameter of shaft shoulder   |
| $d_{b \min}$  | 125 mm | Minimum shaft shoulder               |
| $D_{a \max}$  | 205 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$  | 3 mm   | Maximum recess radius                |
| $r_{a1 \max}$ | 3 mm   | Maximum recess radius                |

### Dimensions

|              |          |                                 |
|--------------|----------|---------------------------------|
| $r_{\min}$   | 4 mm     | Minimum chamfer dimension       |
| $r_{1 \min}$ | 4 mm     | Minimum chamfer dimension       |
| s            | 5 mm     | Axial displacement              |
| E            | 191.5 mm | Raceway diameter outer ring     |
| F            | 123.5 mm | Raceway diameter inner ring     |
| $D_{1 \min}$ | 179.7 mm | Minimum rib diameter outer ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 150 °C | Operating temperature max. |

### Characteristics

|   |                    |
|---|--------------------|
|  | Radial load        |
|  | Grease Lubrication |
|  | Oil Lubrication    |
|  | Not sealed         |