



FAG

**NJ218-E-XL-TVP2**

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-TVP2,  
with cage, single row, semi-locating bearing,  
2 ribs on outer ring, 1 rib on inner ring, type  
NJ

X-life

## Technical information



## Your current product variant

|                           |              |                                  |
|---------------------------|--------------|----------------------------------|
| Design                    | E            | Increased Capacity Design        |
| Cage                      | TVP2         | Solid Window Cage made from PA66 |
| Radial internal clearance | CN (Group N) | Normal internal clearance        |
| Tolerance class           | PN           | Normal (ISO 492:2023)            |
| Number of rows            | 1            | Single-row design                |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 90 mm       | Bore diameter                     |
| D               | 160 mm      | Outside diameter                  |
| B               | 30 mm       | Width                             |
| C <sub>r</sub>  | 215,000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 217,000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 37,500 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 6,000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 3,900 1/min | Reference speed                   |
| m               | 2.36 kg     | Weight                            |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 101 mm | Minimum diameter shaft shoulder      |
| $d_{a \max}$ | 105 mm | Maximum diameter of shaft shoulder   |
| $D_{a \max}$ | 149 mm | Maximum diameter of housing shoulder |
| $d_{c \min}$ | 116 mm | Minimum shaft shoulder               |
| $r_{a \max}$ | 2 mm   | Maximum recess radius                |

### Dimensions

|              |          |                                 |
|--------------|----------|---------------------------------|
| $r_{\min}$   | 2 mm     | Minimum chamfer dimension       |
| $r_{1 \min}$ | 2 mm     | Minimum chamfer dimension       |
| s            | 1.5 mm   | Axial displacement              |
| E            | 145 mm   | Raceway diameter outer ring     |
| F            | 107 mm   | Raceway diameter inner ring     |
| $D_{1 \min}$ | 139.7 mm | Minimum rib diameter outer ring |
| $d_1$        | 114.3 mm | Maximum rib diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Additional information

HJ218-E

L-washer

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed