

**FAG****53211** **Axial deep groove ball bearing**

Axial deep groove ball bearing 532, single direction, with spherical housing washer, steel sheet metal cage

Technical information

**Your current product variant**

Cage	JP	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	55 mm	Inner diameter shaft washer
D	90 mm	Outer diameter housing washer
T	27.3 mm	Height
C_a	58,000 N	Basic dynamic load rating, axial
C_{0a}	133,000 N	Basic static load rating, axial
C_{ua}	6,000 N	Fatigue load limit, axial
n_G	4,350 1/min	Limiting speed
n_{gr}	5,700 1/min	Reference speed
$\approx m$	0.589 kg	Weight

Mounting dimensions

$d_{a \min}$	76 mm	Minimum diameter shaft shoulder
$D_{a \max}$	72 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum filled radius



Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
D_1	57 mm	Inner diameter housing washer
d_1	90 mm	Outer diameter shaft washer
R	72 mm	Radius spherical housing washer
A	35 mm	Distance of the center point
T_1	30 mm	Height with seat washer
D_2	72 mm	Bore diameter seat washer
D_3	95 mm	Outside diameter seat washer
C	9 mm	Height seat washer

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Calculation factors

A	0.11	Minimum load factor
---	------	---------------------

Additional information

U211	Seat washer
------	-------------

Characteristics

	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Static angular error and misalignment