

**FAG****53215**

## Axial deep groove ball bearing

Axial deep groove ball bearing 532, single direction, with spherical housing washer, steel sheet metal cage

## Technical information



## Your current product variant

Cage	JP	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

## Main Dimensions &amp; Performance Data

d	75 mm	Inner diameter shaft washer
D	110 mm	Outer diameter housing washer
T	28.3 mm	Height
$C_a$	67,000 N	Basic dynamic load rating, axial
$C_{0a}$	169,000 N	Basic static load rating, axial
$C_{ua}$	7,700 N	Fatigue load limit, axial
$n_G$	3,950 1/min	Limiting speed
$n_{gr}$	4,300 1/min	Reference speed
$\approx m$	0.812 kg	Weight

## Mounting dimensions

$d_{a \min}$	96 mm	Minimum diameter shaft shoulder
$D_{a \max}$	92 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum filled radius



### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$D_1$	77 mm	Inner diameter housing washer
$d_1$	110 mm	Outer diameter shaft washer
R	90 mm	Radius spherical housing washer
A	49 mm	Distance of the center point
$T_1$	32 mm	Height with seat washer
$D_2$	92 mm	Bore diameter seat washer
$D_3$	115 mm	Outside diameter seat washer
C	9.5 mm	Height seat washer

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Calculation factors

A	0.18	Minimum load factor
---	------	---------------------

### Additional information

U215	Seat washer
------	-------------

### Characteristics

	$F_a$ Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Static angular error and misalignment