

**FAG****52205**

Axial deep groove ball bearing

Axial deep groove ball bearing 522, double direction, steel sheet metal cage

Technical information

**Your current product variant**

Cage	JP	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	20 mm	Inner diameter shaft washer
D	47 mm	Outer diameter housing washer
T ₂	28 mm	Height
C _a	26,500 N	Basic dynamic load rating, axial
C _{0a}	50,000 N	Basic static load rating, axial
C _{ua}	2,280 N	Fatigue load limit, axial
n _G	7,500 1/min	Limiting speed
n _{gr}	9,400 1/min	Reference speed
m	0.214 kg	Weight

Mounting dimensions

d _{a max}	25 mm	Maximum diameter shaft shoulder
D _{a max}	34 mm	Maximum diameter of housing shoulder
r _{a max}	0.6 mm	Maximum filled radius
r _{a1 max}	0.3 mm	Maximum filled radius



Dimensions

D ₁	27 mm	Inner diameter housing washer
B	7 mm	Height shaft washer
r _{min}	0.6 mm	Minimum chamfer dimension
r _{1 min}	0.3 mm	Minimum chamfer dimension






Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Calculation factors

A	0.013	Minimum load factor
---	-------	---------------------

Characteristics

-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed