

**FAG****52318**

Axial deep groove ball bearing

Axial deep groove ball bearing 523, double direction, steel sheet metal cage

Technical information

**Your current product variant**

Cage	JP	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	75 mm	Inner diameter shaft washer
D	155 mm	Outer diameter housing washer
T ₂	88 mm	Height
C _a	193,000 N	Basic dynamic load rating, axial
C _{0a}	455,000 N	Basic static load rating, axial
C _{ua}	18,800 N	Fatigue load limit, axial
n _G	2,240 1/min	Limiting speed
n _{gr}	3,900 1/min	Reference speed
m	6.463 kg	Weight

Mounting dimensions

d _{a max}	90 mm	Maximum diameter shaft shoulder
D _{a max}	116 mm	Maximum diameter of housing shoulder
r _{a max}	1.5 mm	Maximum filled radius
r _{a1 max}	1 mm	Maximum filled radius



Dimensions

D ₁	93 mm	Inner diameter housing washer
B	19 mm	Height shaft washer
r _{min}	1.5 mm	Minimum chamfer dimension
r _{1 min}	1 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Calculation factors

A	1.2	Minimum load factor
---	-----	---------------------

Characteristics

-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed